Marine Air Systems

Working Air Receivers





Your benefits

- High design pressure, therefore suitable for various applications on board.
- Versatile connections for easy installation.
- Hot dip galvanised corrosion protection according to ISO 1461*.
- Approved by all major classification societies: LLR, BV, DNV, ABS, RINA, GL*.
- Including all necessary ancillaries for instance:
 - 100 mm dial Glycerine filled pressure gauge c/w test flange.
 - Drain valve.
 - Safety valve.
- · Horizontal versions on request.

	Volume*	Length (mm)	Diameter (mm)	Weight (kg)	Design Pressure (bar)	Supporting Legs	Inlet (quantity - size)	Outlet (quantity - size)	Drain	Manhole (quantity - size (mm))
	250 liter	1530	500	150	16	included	2 - BSP 1"	2 - BSP 1"	2 - BSP 1/2"	2 - 100 x 150
	500 liter	1930	600	300	16	included	2 - BSP 1"	2 - BSP 1"	2 - BSP 1/2"	2 - 100 x 150
	1000 liter	2370	800	400	16	included	2 - BSP 1 1/2"	2 - BSP 1 1/2"	2 - BSP 1"	2 - 100 x 150
	2000 liter	2420	1100	600	16	included	2 - BSP 1 1/2"	2 - BSP 1 1/2"	2 - BSP 1"	1 - 320 x 420

^{*} Other(s) available on request.



Marine Air Systems

Starting Air Receivers





Your benefits

- · Corrosion protected*
 - Inside: sandblasted SA 2 ½ + Brantho Nitrofest coating.
 - Outside: sandblasted SA 2 ½ + Zinc primer
 & Enamel topcoat.
- Approved by all major classification societies: LLR, BV, DNV, ABS, RINA, GL*.

- · Valve heads included.
- Including all necessary ancillaries for instance:
 - 63 mm dial Glycerine filled pressure gauge c/w test flange.
 - Safety valve.
- · Vertical & horizontal mounting.
- · Feet on request.

Volume	Length (mm)	Diameter (mm)	Weight (kg)	Pressure (bar)	Valve Head	Drain
125 liter	1700	323.9	130	33	VK38	2 - BSP 1/2"
250 liter	1580	480	200	33	VK38	2 - BSP 1/2"
500 liter	3050	480	360	33	VK50	2 - BSP 1/2"
750 liter	2550	650	500	33	VK50	2 - BSP 1/2"
1000 liter	3360	650	650	33	VK50	2 - BSP 1/2"
1500 liter	3350	800	970	33	VK50	2 - BSP 1/2"

^{*} Other(s) available on request.





